



**ToxiPro® with its real-time reading, two-colour visual alarm, and two-tone audible alarm is the single gas detector for “demanding” users**



## Tough durable housing

- Small, lightweight design
- Robust, shock-resistant housing

## Ultra clear backlit display

- Fully illuminated backlit LCD
- Easy to read with clear data display
- Continuous, real-time gas readings
- Max, STEL and TWA readings

## Effective gas alarm indication

- Highly visible bright LED visual alarms (red and yellow)
- Distinctive loud two-tone audible alarm
- Vibration alarm that demands attention in high noise environments

## Designed for tough environments

- IP66/67 rating
- Alarms that demand attention in all hazard locations
- Automatic black box datalogger

## Cost-effective ongoing use

- Field serviceable
- When used with optional IQ Express™ docking station, the ongoing cost of bump testing and calibration is reduced by up to 60%

## Integral datalogging

- Includes a black box datalogger that automatically logs up to 100 sessions
- Can be upgraded to a full datalogger if required

**ToxiPro® is a durable, high performance portable unit designed to offer single gas detection in tough environments. Optimised to deliver enhanced safety to workers and a cost-effective ongoing use over product life, ToxiPro® provides clear alarm status prompts that demand attention.**

Highly visible bright red and yellow LEDs effectively warn users of dangerous conditions, whilst the device's optional vibration alarm ensures workers are alerted to dangers even in high noise environments.

Providing real-time Peak, STEL and TWA readings on a clear backlit LCD display, ToxiPro® includes a black box recorder feature that allows the device to automatically datalog up to 100 sessions, including measurements and time history data.

When used with the ToxiPro® IQ Express™ docking station, the ongoing calibration and bump testing of ToxiPro® can be reduced by up to 60%. The IQ Express™ docking station is able to deliver fully automated bump test, calibration, meter diagnostics and data download, providing considerable savings over product life and reducing the time spent carrying out ongoing maintenance activities.



## Visible alarm lights

1. Normal

3. Danger condition



2. Warning condition

## Optional Accessories

- Replacement sensor filter
- Lanyard
- Replacement belt clip
- Replacement clothes clip
- Replacement mobile phone-style swivel clip
- Manual sample draw kit (includes an adapter, probe and 3m tubing (please note: not for use with Cl<sub>2</sub> and ClO<sub>2</sub>)
- Calibration/sample draw adapter
- Calibration adapter including FEP lined tube for reactive gases (NH<sub>3</sub>, Cl<sub>2</sub>, ClO<sub>2</sub>, HCN and NO<sub>2</sub>)
- IQ Express™ Bump Test and Calibration Station: Includes IQ Express™, 110V power supply, USB cable, software manual, 60 cms (2 ft) tubing with fitting and demand flow
- Four unit mounting bracket for IQ Express™ including tubing and magnetic hardware. (Please note: USB hub, power supply, demand flow regulator and calibration gas not included)
- Four unit mounting bracket for IQ Express™ including tubing, magnetic hardware, and 110V 4X power supply
- ToxiPro® datalogger upgrade (please note: the device must be returned to Honeywell for upgrade)
- ToxiPro® BioTrak software kit including BioTrak software and manual (please note: computer must support IrDA to download)



# General Specification



<b>Housing</b>										
Weight	99 g (3.5oz)									
Size	8.44 cm x 5.56 cm x 2.95 cm (3.325 in. x 2.19 in. x 1.16 in.)									
Case material	Clear polycarbonate with TPE overmold									
Dust and water resistance rating	IP66/IP67									
<b>Environmental ratings</b>										
RF immunity	Conforms to EN 50270									
RF emissions	Conforms to IEC 61000-6-4									
ESD immunity	Conforms to IEC 61000-4-2									
<b>Approvals</b>										
	UL Class I, Div 1, Group A,B,C,D T4 UL Class II, Div 1, Group E,F,G CSA Class I, Div 1, Group A,B,C,D T4 CSA Class II, Div 1, Group E,F,G ATEX (DEMKO) II 1 G Ex ia IIC T4 IECEx Ex ia IIC T4 Ga CE Mark CQST (China) Ex ia IIC T4									
<b>Backlight</b>										
Type	Multi-colour LED backlight									
<b>Gas types</b>										
Available sensors	CO, CO-H, H <sub>2</sub> S, O <sub>2</sub> , SO <sub>2</sub> , PH <sub>3</sub> , NH <sub>3</sub> , CL <sub>2</sub> , HCN, NO <sub>2</sub>									
<b>Alarm levels (default)</b>										
	CO, CO-H	H <sub>2</sub> S	O <sub>2</sub> %	SO <sub>2</sub>	CL <sub>2</sub>	NH <sub>3</sub>	NO <sub>2</sub>	PH <sub>3</sub>	HCN	
Warning alarm (ppm)	35	10	23.5	2	0.5	25	1	0.3	4.7	
Danger alarm (ppm)	100	20	19.5	5	1	35	5	1	4.7	
TWA alarm (ppm)	35	10	na	2	0.5	25	1	0.3	4.7	
STEL alarm (ppm)	100	15	na	5	1	35	1	1	4.7	
<b>Ranges</b>										
	CO	CO-H	H <sub>2</sub> S	SO <sub>2</sub>	O <sub>2</sub>	CL <sub>2</sub>	NH <sub>3</sub>	NO <sub>2</sub>	HCN	PH <sub>3</sub>
	0-999	0-999	0-200	0-100	0-30	0-20	0-100	0-20	0-100	0-20
<b>Resolution</b>										
	CO	CO-H	H <sub>2</sub> S	SO <sub>2</sub>	O <sub>2</sub>	CL <sub>2</sub>	NH <sub>3</sub>	NO <sub>2</sub>	HCN	PH <sub>3</sub>
	1 ppm	1 ppm	1 ppm	0.1 ppm	0.1%/Vol	0.1 ppm	1 ppm	0.1 ppm	0.1 ppm	0.01 ppm
<b>Battery</b>										
Battery life	9000 hours									
Shelf life	4000 hours									
Type	Lithium Manganese Dioxide									
Battery replaceable	Yes									
Reverse battery protection	Yes									
<b>Datalogging</b>										
Number of sessions	up to 100									
Number of intervals	up to 8100									
Number of events	100									
Black box datalogger	up to 8100 intervals at one minute Can be upgraded to a full datalogger at any time. Activation code and BioTrak PC software required									
<b>Instrument</b>										
Temperature range	(Continuous — storage) 0 to 110°F (-18 to 43°C)									
Temperature range	(Intermittent <30 minutes; H <sub>2</sub> S) -40 to 140°F (-40 to 60°C)									
Temperature range	(Intermittent <30 minutes; Others) -20 to 120°F (-29 to 49°C)									
Humidity range	15 - 95% RH, non-condensing (0 - 95% RH <= 4 hours)									
Alarm sound levels (two-tone)	102 dB @ 10 cm									

# Our Product Range



## Fixed Gas Monitoring

Honeywell Analytics offers a wide range of fixed gas detection solutions for a diverse array of industries and applications including: Commercial properties, industrial applications, semiconductor manufacturers, energy plants and petrochemical sites.

- » Detection of flammable, Oxygen and toxic gases (including exotics)
- » Innovative use of four core sensing technologies – paper tape, electrochemical cell, catalytic bead and infrared
- » Capability to detect down to Parts Per Billion (ppb) or Percent by Volume (%v/v)
- » Cost effective regulatory compliance solutions

## Portable Gas Monitoring

When it comes to personal protection from gas hazards, Honeywell Analytics has a wide range of reliable solutions ideally suited for use in confined or enclosed spaces.

These include:

- » Detection of flammable, Oxygen and toxic gases
- » Single gas personal monitors – worn by the individual
- » Multi-gas portable gas monitors – used for confined space entry and regulatory compliance
- » Multi-gas transportable monitors – used for temporary protection of area during site construction and maintenance activities

## Technical Services

At Honeywell Analytics, we believe in the value of great service and customer care. Our key commitment is providing complete and total customer satisfaction. Here are just a few of the services we can offer:

- » Full technical support
- » Expert team on hand to answer questions and queries
- » Fully equipped workshops to ensure quick turnaround on repairs
- » Comprehensive service engineer network
- » Training on product use and maintenance
- » Mobile calibration service
- » Customised programmes of preventative/corrective maintenance
- » Extended warranties on products

### Contact information for orders (sales & service)

Life Safety Distribution AG  
Javastrasse 2  
8604 Hegnau  
Switzerland  
Tel: +33 (0)4 42 98 17 70  
Fax: +33 (0)4 42 71 97 05  
PortablesFR@honeywell.com (for sales requests)  
BIOexpert@honeywell.com (for service requests)

### Contact information for service returns

Life Safety Distribution AG  
c/o Honeywell Portable Gas Detection  
ZAC Athélia 4 - 375 avenue du Mistral  
Bât B, Espace Mistral  
13600 La Ciotat, France  
Tel: +33 (0)4 42 98 17 70  
Fax: +33 (0)4 42 71 97 05  
BIOexpert@honeywell.com (for service requests)

[www.honeywell.com](http://www.honeywell.com)

#### Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

H\_ToxiPro\_DS01117\_V3\_EMEAI

08/12

© 2012 Honeywell Analytics

# Honeywell